


LABELMATE USA

Label Handling Innovations


FULL SIZE DIGITAL LABEL COUNTERS



RRC-250 with 3"
Unwind & Rewind Shafts.
HWD: 13" x 25" x 10"
(330-mm x 635-mm x 254-mm)



RRC-330-UA with 3" Unwind
and Adjustable 1"- 4" Rewind Shaft.
HWD: 13" x 32.5" x 13"
(330-mm x 826-mm x 330-mm)



RRC-330-US
Ultrasonic Reel-to-Reel Counter uses
an ultrasonic detector to count almost
any type of label, including transparent,
semi-transparent and opaque labels.
HWD: 14.5" x 32.5" x 13"
(368-mm x 826-mm x 330-mm)

Key Features & Benefits

- Built-in 6-Digit Preset-Counter with Auto-Stop when Preset Count is reached or Out-of-Labels.
- Digital Controller for accurate and repeatable counts.
- Wind-In" or "Wind-Out" to reverse facing of labels.
- Label width: Up to 6" (152-mm). Adjustable Label Guide helps realign uneven label rolls. 10" width available
- Rugged Construction. Worldwide 100-240V 50-60Hz Power Supply.
- Rewind speed varies with roll diameter and weight. Durable 3" (76-mm) i.d. fin-style Unwind Core holders.

REWIND CORE I.D.	ROLL DIA.	SPEED	DESCRIPTION	MODEL
3" (76-mm)	10" (254-mm)	Up to 80"/sec	Self-contained Reel-to-Reel Label Counter. For opaque labels with gap between only.	RRC-250
3" (76-mm)	13" (330-mm)	Up to 92"/sec	As above but with 13" (330-mm) Roll Diameter capacity. For opaque labels only.	RRC-330
1" - 4" adjustable	13" (330-mm)	Up to 92"/sec	As above but with an Adjustable 1" to 4" Rewind Core Holder.	RRC-330-A
3" (76-mm)	13" (330-mm)	Up to 92"/sec	Universal Reel-to-Reel Counter for any label, transparent, opaque, and very narrow labels. Bonus Feature! Count "butt-cut" labels and measure linear distances.	RRC-330-U
3" (76-mm)	13" (330-mm)	Up to 92"/sec	Universal Reel-to-Reel Counter as above, but with a 1" to 4" Adjustable Rewind Core .	RRC-330-UA
3" (76-mm)	13" (330-mm)	Up to 92"/sec	Ultrasonic Reel-to-Reel Counter for transparent, semi-transparent and opaque, labels. Minimum label width 1" (25.4-mm). Must have a gap between labels.	RRC-330-US
1" - 4" adjustable	13" (330-mm)	Up to 92"/sec	Ultrasonic Reel-to-Reel Counter as above, but with a 1" to 4" Adjustable Rewind Core Holder .	RRC-330-USA
OPTIONS FOR RRC COUNTING SYSTEMS				
Extra Unwind Shaft for 1" Cores. Change from the standard 3" Core Holder in minutes.				RR-1"U
Extra Unwind Shaft for 1.5" Cores. Change from the standard 3" Core Holder in minutes.				RR-1.5"U
Extra Unwind Shaft for 40-mm Cores. Change from the standard 3" Core Holder in minutes.				RR-40mmU